

**FLUTEC Dyed Blue Density 1.88**

**1 – Identification of the preparation and the company**

Trade name: FLUTEC Dyed Blue Density 1.88  
 REACH registration name: None  
 REACH registration number: None  
 Primary uses: Instrument indicator fluid  
 Company: F2 Chemicals Ltd.  
 Address: Lea Lane, Lea Town  
 Preston, PR4 0RZ, UK  
 Telephone: +44 (0) 1772 775804  
 Fax: +44 (0) 1772 775809  
 Emergency telephone: +44 (0) 1772 775833  
 E-mail: safety@f2chemicals.com

**2 – Hazards identification**

**Classification as per EU-GHS Ordinance (EC) No. 1272/2008**

*Non-hazardous*

GHS Labelling  
 Signal word: None.  
 Pictograms: None.

**Classification as per Directive 67/548/EEC or Directive 1999/45/EC**

*Non-hazardous*

**3 – Composition/information on ingredients**

Substances	Concentration	CAS No.	EC-No.
1. Blue dye	0.008%	-	-
2. FLUTEC Dyed Blue Density 1.88 (1,1,2,3,3,4,5,5,6-Decafluoro-2,4,6-tris(trifluoromethyl)cyclohexane)	Remainder	374-76-5	417-270-4

**4 – First-aid measures**

a) Inhalation: FLUTEC fluids are considered not to have significant acute toxicity by inhalation.  
 b) Skin contact: FLUTEC fluids are considered to be non-irritating to skin.  
 c) Eye contact: FLUTEC fluids are considered to be non-irritating to eyes.  
 d) Ingestion: FLUTEC fluids are considered not to have significant acute oral toxicity.

### 5 – Fire-fighting measures

- a) Suitable extinguishers: Any.
- b) Unsuitable extinguishers: None.
- c) Hazardous decomposition: Toxic fumes, including hydrogen fluoride fumes, may be produced on thermal decomposition, such as contact with flames, and in particular where hydrogen-containing compounds are also present.
- d) Protective equipment: Use approved self-contained breathing apparatus.

### 6 – Accidental release measures

- a) Personal precautions: Wear laboratory coat.  
Respiratory protection not normally required.  
Wear gloves (any chemically-resistant gloves are suitable).  
Wear safety spectacles or goggles.  
FLUTEC Dyed Blue Density 1.88 spillages can produce very slippery surfaces which may be hazardous to personnel.
- b) Environmental precautions: Do not allow spillage to enter drains or watercourse.  
If water is contaminated inform relevant authority immediately.
- c) Method of clean-up: Absorb in inert material eg. sand, vermiculite absorbent granules, place in plastic container for transfer. The blue stain can be removed using a solvent such as acetone (as long as the surface is compatible with the solvent).

### 7 – Handling and storage

- a) Handling: Do not smoke, eat or drink when handling.  
Avoid contact of vapour or liquid with red hot surfaces, flames or electrical arcs as this may give rise to toxic gases such as hydrogen fluoride.  
Do not use sodium or similar metals or their hydrides for removing water from the liquid; other desiccants are acceptable.  
Where applicable, systems should be designed to reduce the risk of releases to the atmosphere.
- b) Storage: Store in original, tightly closed, labelled container.

### 8 – Exposure controls and personal protection

- a) Exposure limit values: None.
- b) Exposure controls: Recommend using in a well-ventilated area.
- c) Occupational exposure: Light eye protection (safety glasses) and gloves (any chemically resistant gloves are suitable).
- d) Environmental exposure: Where applicable, use in closed systems, or systems with vapour returns.

## 9 – Physical and chemical properties

*Where applicable (and noted), this refers to the solvent, Perfluoro-1,3,5-trimethylcyclohexane, rather than the mixture.*

Appearance:	Clear, colourless liquid
Odour:	Odourless
pH	n/a
Pour point (melting point):	<0°C
Boiling point (solvent):	127.4°C
Flash point:	Non-flammable
Evaporation rate:	Fast
Explosive limits:	None
Vapour pressure (solvent):	1.3 kPa @ 25°C
Vapour density (solvent):	ca. 0.014 kg/l @bp
Relative density (solvent):	1.888 @ 25°C
Solubility in water:	Insoluble (< 25 ppm)
Solubility in organic solvents:	Sparingly soluble in most common solvents. Miscible with CFCs.
Partition co-efficient:	No data
Auto-ignition temperature:	None
Decomposition temperature:	>400°C
Dynamic viscosity (solvent):	2.3 mPa s @ 25°C
Explosive properties:	None
Oxidising properties:	None

## 10 – Stability and reactivity

a) Reactivity:	Very low reactivity.
b) Chemical stability:	Stable indefinitely at ambient conditions.
b) Conditions to avoid:	Naked flames, hot surfaces (>400°C).
c) Incompatible materials:	Reacts with lithium, sodium, potassium, calcium, and barium.
d) Hazardous decomposition:	High temperatures can give rise to toxic fumes, including hydrogen fluoride.

## 11 – Toxicological information

The solvent has been assessed on adequate evidence and found to produce either no effect or an effect below the threshold for classification.

The toxicological properties of the blue dye have not been fully established. This preparation has been evaluated on a "best guess", taking into account the very low concentration of the dye, as well a reasoned estimate of the toxicity of the dye. Nevertheless, F2 Chemicals Ltd would advise that the material be handled with caution.

## 12 – Ecological information

- a) Ecotoxicity: No specific data available.
- b) Mobility: Volatile; material readily lost to the atmosphere.  
Low surface tension; material readily able to seep into ground water.
- c) Persistence: Material liable to persist in the environment for considerable time; not subject to biodegradation.
- d) Bioaccumulation: Material not expected to accumulate in biota.

## 13 – Disposal considerations

Observe all national and regional regulations.  
Do not discharge into drains or watercourses.  
Small quantities can be sent to an authorised landfill site.  
Larger quantities should be incinerated by a licensed waste disposal organisation at a site equipped with an after burner and scrubber.

## 14 – Transport information

This material is not regulated by IATA/ICAO (air), ADR (road), IMDG (sea) or RID (rail).  
There is no applicable UN number, class or transport name.

## 15 – Regulatory information

- a) Chemical safety assessment: Not yet available.
- b) GHS P-phrases: P370: In case of fire: Do not breath fumes.
- c) R- and S-Phrases: S41: In case of fire and/or explosion do not breathe fumes.

## 16 – Other information

- a) Precautionary phrases: P260: Do not eat, drink or smoke when using this product.  
P370: In case of fire: Do not breathe fume.
- b) Suitability for purpose: F2 Chemicals Ltd cannot guarantee the suitability of this material for any particular purpose. It is the responsibility of the customer to satisfy himself that the product is suitable for his purpose. In the event of doubt the customer may contact F2 Chemicals for advice.
- c) Revision: This version, CLP-1.0, has been revised for CLP, November 2010, and the changes are all associated with reformatting and modifying for that purpose. There are no changes to the risks, hazards or properties of the material. This version replaces all previous versions.